# Jacobsen®

## **Product Information Declaration**

## **Jacobsen J-System Installation Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Jacobsen J-System Installation

#### **Scope and Limitations of Intended Use**

×	Residential	×	Commercial
×	High Traffic	×	Low Traffic
×	Antistatic Environment	×	Food Prep Areas
×	Ramp/Entry	×	Under Floor Heating

#### **Identifiers**

See individual sku codes under identifiers

X	Interior
×	Exposed Sunlight
×	Clean Room

**Over Existing Floor** 

X Exterior

X Wet Areas

X With Wheels

## B

#### Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	-
Industrial	_

#### **C** Protection from Fire

Relevant NZBC Clause Product Performance

X

C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	-	

### D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## Ε

#### Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

## F

#### Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	-
	-
	Phthalate-free

Indoor Air Quality

## **G** Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## H Energy Efficiency

Relevant NZBC Clause Product Performance

Thermal Rating

### **X** Warnings and Bans

Building Act 2004 Product Performance

Section 26

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## **Product Information Declaration** Jacobsen J-System Installation Range

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that Jacobsen J-System Installation is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration** Jacobsen J-System Installation Range

#### **Identifiers**

This JPID covers all colours from Jacobsen J-System Installation including:

J-System 33 Low Slump Levelling Compound 25226 J-System 32 Fine Finish Compound 25225 J-System 31 Self Levelling Compound 25224 J-System 21 Concrete Primer 25223 J-System 13 High Moisture Acrylic Adhesive 25222 J-System 12 Pressure Sensitive Carpet Tile Adhesive 25221 J-System 11 Vinyl Floor and Wall Acrylic Adhesive 25214

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Deceler	-	
Embodied Carbon Emission Data		_

#### **Environmental Credentials**

## Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: Jacobsen Country of Origin: Germany