# **Jacobsen**<sup>®</sup>

### **Product Information Declaration**

## **Tredsafe Detail Trims Carpet to Vinyl Height Transition Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as Tredsafe Detail Trims Carpet to Vinyl Height Transition

#### . . . **Scope and Limitations o**

~	Residential
---	-------------

- **High Traffic**

Antistatic Environment

Ramp/Entry

of Intended Use		
	~	Commercial
	~	Low Traffic
	~	Food Prep Areas

X Under Floor Heating

**Identifiers** 

See individual sku codes under identifiers

- Interior
- Exposed Sunlight
- Clean Room
- Over Existing Floor
- Exterior
- Wet Areas
- With Wheels

#### B **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	5 Years
Industrial	_

#### С **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-

```
C4.3 (b) Floor
```

## Access

ACCESS	
Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution

Suitable for food prep

## Ε

#### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

### F **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	Not Tested
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	-

#### G **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

#### н **Energy Efficiency**

Relevant NZBC Clause	Product Performance

Thermal Rating

Not tested

X Warnings and Bans

Building Act 2004 Product Performance

Section 26

True

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## Product Information Declaration Tredsafe Detail Trims Carpet to Vinyl Height Transition Range

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **Tredsafe Detail Trims Carpet to Vinyl Height Transition** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration Tredsafe Detail Trims Carpet to Vinyl Height Transition Range**

#### Identifiers

This JPID covers all colours from Tredsafe Detail Trims Carpet to Vinyl Height Transition including:

DT040 11967	DT029 11951
DT084 11999	DT037 11963
DT039 11966	DT036 11962
DT039 11965	DT035 11961
DT038 11964	DT035 11960
DT034 11959	DT027 11949
DT033 11958	DT024 11946
DT030 11953	DT023 11944
DT030 11952	DT022 11943

# Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328



Product Manufacturer: **Tredsafe** Country of Origin: New Zealand