

Product Information Declaration

Shaw Contract Spark Tile Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Shaw Contract Spark Tile

Identifiers

X Over Existing Floor

See individual sku codes under identifiers

Scope and Limitations of Intended Use

| × | Residential | × | Commercial | × | Interior | × | Exterior |
|---|------------------------|---|------------------------|---|------------------|---|----------------------|
| × | High Traffie | × | Low Traffie | × | Exposed Sunlight | × | Wet Areas |
| × | Antistatic Environment | × | Food Prep Areas | × | Clean Room | × | With Wheels |

R

Stability

X Ramp/Entry

| Relevant NZBC Clause | Product Performance | | |
|----------------------|---------------------|--|--|
| B2.3.1(c) | - | | |
| Residential | - | | |
| Commercial | - | | |
| Industrial | - | | |

X Under Floor Heating

Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| C4.3 | |
| C4.3 (a) Wall | - |
| C4.3 (b) Floor | - |

Access

| Relevant NZBC Clause | Product Performance | | |
|------------------------|---------------------|--|--|
| D1.3.3 | | | |
| Level Surface (Wet) | - | | |
| Level Surface (Dry) | - | | |
| Suitable for food prep | - | | |

E

Moisture

| Relevant NZBC Clause | Product Performance | | |
|----------------------|-------------------------------|--|--|
| E3.3.3 | Impervious and easily cleaned | | |
| E3.3.5 | Impervious and easily cleaned | | |
| E3.3.6 | Water resistant | | |
| NZBC/AS1 | - | | |

F

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| F2.3.1 | - |
| | - |
| | Phthalate-free |
| Indoor Air Quality | - |

G

Services and Facilities

| Product Performance |
|---------------------|
| Water resistant |
| - |
| |

Н

Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating | - |



Warnings and Bans

| Building Act 2004 | Product Performance | | |
|-------------------|---------------------|--|--|
| Section 26 | - | | |

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:160524

Product Information Declaration Shaw Contract Spark Tile Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Shaw Contract Spark Tile** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:160524

Product Information Declaration Shaw Contract Spark Tile Range

Identifiers

This JPID covers all colours from Shaw Contract Spark Tile including:

Flair-Color 5T489-87675 Flourish 5T489-87580 Moxie 5T489-87535 Brio 5T489-87518 Vibrance 5T489-87510 Gusto 5T489-87500 Brio-Color 5T489-87485 Moxie-Color 5T489-87411 Vitality-Color 5T489-87375 Vibrance-Color 5T489-87327 Flourish-Color 5T489-87326 Vitality 5T489-87105 Flair 5T489-87100

Sustainability

| Rating System | Rating | Product Performance |
|-----------------------------------|-------------------|--------------------------------|
| Green Star Design & | Credit 12 | 1 Point |
| As Built NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star | Credit 13 | 1 Point |
| Interiors NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 1 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | 1 Point |
| | EN 3 | 1.5 Points |
| Homestar V4 | Mat-1 | 2 Points |
| | Mat-2 | 1 Point |
| Environmental Product De | eceleration (EPD) | Yes |
| Embodied Carbon Emissi | on Data | - |

Environmental Credentials









Declare.











Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

ShawContract®

Product Manufacturer: Shaw Contract Country of Origin: -

Page 3 of 3 V:160524