Jacobsen[®]

Product Information Declaration

Winckleman Wincklemans Range

Range Description

Antistatic Environment

This Jacobsen Product Information Declaration (PID) applies to the ceramic & porcelain tiles range sold by Jacobsen as Winckleman Wincklemans

Product Performance

10 years

_

-

Scope and Limitations of Intended Use

✓	Residential
x	High Traffic

- Х Low Traffic
 - Х Food Prep Areas

Commercial

./ **Under Floor Heating**

С

C4.3



Product Performance

Identifiers

See individual sku codes under identifiers

X Exterior

Wet Areas

With Wheels

X Ramp/Entry

Stability

B2.3.1(c)

Residential

Commercial

Industrial

Relevant NZBC Clause

Х

B

Х **Over Existing Floor**

_

D Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	R10	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

Ε

Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

F

C4.3 (a) Wall

C4.3 (b) Floor

Safety of Users

Protection from Fire

Relevant NZBC Clause

Relevant NZBC Clause	Product Performance	
F2.3.1	No VOC's	
	Does not encourage bacterial growth	
_	Phthalate-free	
Indoor Air Quality	Optimal	

G **Services and Facilities**

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	-	

Н **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Winckleman Wincklemans Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that Winckleman Wincklemans is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Winckleman Wincklemans Range

Identifiers

This JPID covers all colours from Winckleman Wincklemans including:

White 50 x 50mm Mosaic Tile 265x530 WINCMOS1271 Red 50 x 50mm Mosaic Tile 265x530 WINCMOS1269 Pale Grey Stackbond 23 x 50mm Mosaic Tile 316x316 WINCMOS1275 Pale Blue 50 x 50mm Mosaic Tile 265x530 WINCMOS1266 Pale Green 50 x 50mm Mosaic Tile 265x530 WINCMOS1267 Charcoal 50 x 50mm Mosaic Tile 265x530 WINCMOS1258 Charcoal 23 x 50mm Stackbond Mosiac Tile 316x316 WINCMOS1276 Black 23 x 50mm Stackbond Mosaic Tile 316x316 WINCMOS1278 Black 50 x 50mm Mosaic Tile 265x530 WINCMOS1257

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		-

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: Winckleman Country of Origin: France