Product Information Declaration

Refin Block Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the ceramic & porcelain tiles range sold by Jacobsen as Refin Block

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

| <u> </u> | Residential |
|----------|------------------------|
| / | High Traffic |
| × | Antistatic Environment |

- Commercial Low Traffic Food Prep Areas
- Interior **Exposed Sunlight** Clean Room
- Exterior Wet Areas

With Wheels

X Ramp/Entry

Under Floor Heating

Over Existing Floor

Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| B2.3.1(c) | 10 Years |
| Residential | Suitable |
| Commercial | Suitable |
| Industrial | - |

Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|--------------------------|
| C4.3 | |
| C4.3 (a) Wall | Naturally Fire Resistant |
| C4.3 (b) Floor | Naturally Fire Resistant |

Access

| Relevant NZBC Clause | Product Performance |
|------------------------|---------------------|
| D1.3.3 | |
| Level Surface (Wet) | R10 |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------------|
| F2.3.1 | No VOC's |
| | Does not encourage bacterial growth |
| | Phthalate-free |
| Indoor Air Quality | Optimal |

Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b) | Water resistant |
| G6.3.2 | - |
| | |

Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------|
| Thermal Rating | Compliant (ISO 10545/9) |

X

Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26 | - |

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:160524

Product Information Declaration Refin Block Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Refin Block** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:160524

Product Information Declaration Refin Block Range

Identifiers

This JPID covers all colours from Refin Block including:

Nickel 600mm x 600mm 23960 Mist 600mm x 600mm 14891 Iron 600mm x 600mm 14890 Cinder 600mm x 600mm 14889

Sustainability

| Rating System | Rating | Product Performance |
|--|-----------|-----------------------------------|
| Green Star Design & | Credit 12 | - |
| As Built NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star | Credit 13 | - |
| Interiors NZ (V1) | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | 1 Point |
| | EN 3 | 1.5 Points |
| Homestar V4 | Mat-1 | 2 Point |
| | Mat-2 | 1 Point |
| Environmental Product Deceleration (EPD) | | Yes |
| Embodied Carbon Emission Data | | 9.6 kgCO2e / m2 (Cradle to Gate) |

Environmental Credentials















Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

REFIN

Product Manufacturer: Refin Country of Origin: Italy

Page 3 of 3 V:160524