## **Product Information Declaration**

## **Regupol Classic Range**

### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as **Regupol Classic** 

### **Identifiers**

See individual sku codes under identifiers

### **Scope and Limitations of Intended Use**

$\overline{}$	Autistatia Farriga anno at
<b>/</b>	High Traffic
<u>~</u>	Residential

✓ Commercial

X Low Traffic

X Food Prep Areas

✓ Interior
✓ Exposed Sunlight
X Clean Room

X Exterior
X Wet Areas

With Wheels

Under Floor Heating

★ Over Existing Floor

### B

### **Stability**

X Ramp/Entry

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years
Residential	Extra Heavy Duty
Commercial	Extra Heavy Duty
Industrial	Heavy Duty

## C

### **Protection from Fire**

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	4mm - CRF 6.2 kW/m2 (ISO 9239.1:2010), 8mm CRF 5.0 kW/m2 (ISO 9239.1:2010)	

## D

### Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	SRV 39 (AS4586:2013)	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

## E

## Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F

### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	2.3 mg/m2/hr ASTM D5116
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Good

## G

### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	Approx. 19dB ISO 140

## H

### **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thermal Rating	Good



### **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

## **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:010524

# **Product Information Declaration Regupol Classic Range**

### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55

### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Note**

It is expected that **Regupol Classic** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:010524

# **Product Information Declaration Regupol Classic Range**

### **Identifiers**

This JPID covers all colours from Regupol Classic including:

Sidon (Core) 4mm 11771
Goa (Core) 4mm 11770
Manaus (Core) 4mm 11768
Palau (Core) 4mm 11767
Amsterdam (Core) 4mm 11765
Berlin (Core) 4mm 11769
Goa (Core) 8mm 11784
Melbourne (Core) 8mm 11782
Amsterdam (Core) 8mm 11779
Palau (Core) 8mm 11779
Palau (Core) 8mm 11778
Berlin (Core) 8mm 11777
Berlin (Core) 8mm 11777
Berlin (Core) 8mm Tile 11789
Mons (Core) 4mm 11766

Melbourne (Core) 4mm RGCLME4
Auckland (Core) 4mm RGCLAU4
Perth (Tone) 8mm RGCLPE8
Lhasa (Tone) 8mm RGCLLH8
Perth (Tone) 4mm RGCLPE4
Lhasa (Tone) 4mm RGCLLH4
Sydney (Tone) 8mm RGCLSY8
Nome (Tone) 8mm RGCLSY8
Nome (Tone) 8mm RGCLNO8
Kush (Tone) 8mm RGCLNU8
Bern (Tone Berlin) 8mm RGCLBE8
Auckland (Tone) 8mm RGCLAU8
Sydney (Tone) 4mm RGCLSY4
Nome (Tone) 4mm RGCLNO4
Kush (Tone) 4mm RGCLNU4
Bern 4mm (Tone) RGCLBE4

### **Sustainability**

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4 Mat-1		2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		-

### **Environmental Credentials**

















## **Jacobsen®**

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328



Product Manufacturer: Regupol Country of Origin: DEU

Page 3 of 3 V:010524