Jacobsen®

Product Information Declaration Regupol Diamond Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the rubber range sold by Jacobsen as **Regupol Diamond**

Scope and Limitations of Intended Use

Residential	✓ Commercial
High Traffic	× Low Traffic
Antistatic Environment	X Food Prep Areas
Ramp/Entry	X Under Floor Heating

Identifiers

See individual sku codes under identifiers

✓ Interior ✓ Exposed Sunlight X Clean Room

X Over Existing Floor

- X Exterior
- X Wet Areas
- With Wheels

B

✓ | ✓ | × | ×

Sta	bil	ity	

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years
Residential	Extra Heavy Duty
Commercial	Extra Heavy Duty
Industrial	Heavy Duty

C Protection from Fire

Relevant NZBC Clause Product Performance

C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	-	

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

Ε

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

F

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	2.3 mg/m2/hr (ASTM D5116)
	Does not encourage bacterial growth
	Phthalate-free
ndoor Air Quality	Good

H Energy Efficiency

Fnordy	ETTICIONCV
LICIGY	Efficiency
	· · · · · · · · · · · · · · · · · · ·

Relevant NZBC Clause	Product Performance
Thermal Rating	Good

X Warnings and Bans

Building Act 2004 Product Performance
Section 26 -

G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	Approx. 14dB ISO 140

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Regupol Diamond Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that **Regupol Diamond** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Regupol Diamond Range

Identifiers

This JPID covers all colours from Regupol Diamond including:

Mons Diamond 4mm E1081

Berlin Diamond 4mm E1075

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	_
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.5
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product D	eceleration (EPD)	-
Embodied Carbon Emissi	ion Data	-

Environmental Credentials



PVC FREE RECYCLABLE



Product Manufacturer: **Regupol** Country of Origin: DEU

Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328