Jacobsen®

Product Information Declaration

Tarkett Acczent Excellence Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Tarkett Acczent Excellence**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ ~~Exterior~~
✓ High Traffic	✗ ~~Low Traffic~~	✓ Exposed Sunlight	✗ ~~Wet Areas~~
✗ ~~Antistatic Environment~~	✗ ~~Food Prep Areas~~	✗ ~~Clean Room~~	✓ With Wheels
✗ ~~Ramp/Entry~~	✓ Under Floor Heating	✗ ~~Over Existing Floor~~	

B
Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 18074)
Industrial	43 (ISO 18074)

C
Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CRF 8.12 kW/m2 (ISO 9239-1)

D
Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	Refer to Slip Test Summary Sheet
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E
Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F
Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10¬µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G
Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	delta Lw 3 dB (EN ISO 717-2)

H
Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.02m2 K/W (EN ISO 10456)

X
Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code

Product Information Declaration
Tarkett Acczent Excellence Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Acczent Excellence** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration
Tarkett Acczent Excellence Range

Identifiers

This JPID covers all colours from Tarkett Acczent Excellence including:

Triangle Wood Chalk E25128136
Soft Water E25128134
Warm Grey E25131925
Dark Beige E25131918
Medium Grey 24481
Brushed Grey E25130100
Allover Wood White E25129714
Allover Wood Black E25129713
Carpet Intense Olive E25128106
Terrazzo Blue E25128105
Terrazzo Terracotta 0104 E25128104
Tissage Soft Orange E25128132
Tissage Soft Light Green E25128131
Tissage Soft Light Blue E25128130
Tissage Soft Beige E25128129
Tissage Soft Grege E25128128
Tissage Soft Grey E25128127
Tapped Metal Grey 0126 E25128126
Dark Grey 24477
Matrix Bright Orange 0188 E25131188
Matrix Bright Anis 0186 E25131186
Matrix Bright Turquoise 0185 E25131185
Matrix Dark Grey 1019 E25131019
Matrix Graphite E25131000
Digital Wave Grey Anis E25130184
Allover Wood Grege 12212
Scandinavian Medium Beige 0403 E25129403
Scandinavian Light Beige 0402 E25129402
Scandinavian Medium Grey 0401 E25129401
Scandinavian Oak Dark Grey 0400 E25129400
Oak Tree Grey 0202 E25129202
Oak Tree Beige 12211
Serene Oak Dark Brown 0512 22224
Serene Oak Warm Brown 0511 E25204511
Serene Oak Red Brown 0510 E25204510
Serene Oak Brown Grey 0509 E25204509
Terrazzo Green 0103 E25128103
Esquisse Light Chocolate E25128017
Esquisse Dark Grey E25128015
Esquisse Medium Grey E25128014
Esquisse Light Grey E25128013
Esquisse Grey Beige E25128012
Natural E25127818
Diamond Blue E25128123
Facet Prune E25128121
Facet Blue 12205
Digital Wave Grey E25130183
Digital Wave Grey Ice Blue E25130182
Modern Oak Natural 19011
Modern Oak Grege 12209
Modern Oak White E25129005
Concrete Steel Blue E25128507
Concrete Warm Grey E25128504
Concrete Grey Beige E25128503
Serene Oak Medium Grey 0508 E25204508
Intense Jean 23267
Intense Terracotta 22944
Bright Extreme Blue E25131941
White 24483
Black 23913
White E25127817
Beech Longstripe Light 21993
Brushed Oak Light E25127027
Brushed Oak Medium E25127026
Oak Longstripe Natural 7002 19088
Oak Longstripe Light 7001 21484
Matrix Phospho 0101 E25032101
Facet Black & White E25128118
Facet Mid Grey E25128116
Facet Water E25128115
Fusion Lines Intense Olive E25130175
Fusion Lines Intense Petrole E25130174
Fusion Lines Beige E25130173
Fusion Lines Dark Grey E25130172
Fusion Lines Phospho E25130171
Concrete Chalk E25128502
Concrete Dark Grey 12207
Concrete Grey Beige 19007
Fiber Wood Natural E25128303
Fiber Wood Grege E25128302
Encryption Black & White E25128189
Flocons 2 Rainbow E25128170
Intense Olive E25131938
Intense Water E25131936
Intense Petrole E25131935
Intense Kaki 24480
Bright Dark Turquoise E25131933
Bright Ice Blue E25131932
Modern Oak Natural Brown E25029009
Granito Cool Grey 23011
Granito Warm Grey 21451
Granito Light Beige E25128109
Carpet White Grey E25128108
Carpet Intense Jean 12204
Cubic Intense Petrole E25130166
Cubic Bright Anis E25130164
Bubbles Cold Mix E25130143
Modern Maple Maple 0141 22191
Indigo E25128140
Turquoise E25128139
Dark Grey 21450
Triangle Wood Natural E25128137
Bright Anis E25131931
Bright Yellow 24034
Bright Orange E25131929
Bright Red 24474
Bright Pink E25131927
Bright Turquoise E25131926

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		8.78 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacoben.co.nz

NZBN:
9429040403328

Tarkett

Product Manufacturer: **Tarkett**
Country of Origin: France