# Jacobsen®

## **Product Information Declaration**

## **Tarkett Eclipse Premium Spirit Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Eclipse Premium Spirit

#### **Scope and Limitations of Intended Use**

Residential	<ul> <li>Commercial</li> </ul>
High Traffic	× Low Traffic
Antistatic Environment	✓ Food Prep Areas
Ramp/Entry	X Under Floor Heating

#### **Identifiers**

See individual sku codes under identifiers

Interior Exposed Sunlight Clean Room

Х **Over Existing Floor** 

- Х Exterior
- Х Wet Areas
- With Wheels

## B

× v x x

#### **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 Years
Residential	-
Commercial	34 Very Heavy
Industrial	43 Heavy

#### С **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 3 (ISO 5660.1-2002)
C4.3 (b) Floor	CRF 10kW/m2 , (ISO 9239-1:2010)

### D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 52 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## Ε

#### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 10 µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
_	Phthalate-free
Indoor Air Quality	Optimal

### G **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

### н **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thermal Rating	Approx. 0.01 m2 K/W

### X **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## **Product Information Declaration** Tarkett Eclipse Premium Spirit Range

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **Tarkett Eclipse Premium Spirit** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration** Tarkett Eclipse Premium Spirit Range

#### Identifiers

This JPID covers all colours from Tarkett Eclipse Premium Spirit including:

Light Orange 23434 Orange 12309 Red 26506 Light Red 23210 Red Purple 25321 Midnight Blue 12308 Light Ocean Blue 12307 Ocean Blue 12306 Green 12305 Light Olive Green 23432 Dark Brick E21020768 Clay Grey 12328 Medium Blue 12324 Light Blue 12323 Medium Green 12322 Light Green 12321 Dark Warm Beige 12320 Medium Warm Beige 12319 Sand 12304

Yellow 12303 MD Blue E21020730 Dark Brown 12302 Dark Clay Grey 21147 Medium Grey 19099 Light Beige 12318 Medium Cool Beige 12316 Light Cool Beige 12315 Dark Cool Grey 12314 Medium Cool Grey 12313 Grey 12312 Medium Pure Grey 12311 Warm Grey 12301 Dark Warm Grey 12300 Black 12299 Light Grey 12298 Light Pure Grey 12310 Light Yellow 20809

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product	Deceleration (EPD)	Yes
Embodied Carbon Emiss	ion Data	5.71 kgCO2eq / m2 (Cradle to Gate)

#### **Environmental Credentials**



# **O** Tarkett

Product Manufacturer: Tarkett Country of Origin: Sweden

# Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328