



**JACOBSEN
BRINGS YOU**

**SELECT
STRATAWORX**


Commercial Carpet Tiles
NZ Stock Ranges




Poured Strataworx Mortar




Poured Strataworx Aggregate




Poured Strataworx Granite




Poured Strataworx River Rock




Diffuse Strataworx Train Station




Diffuse Strataworx Magnetic Fields




Surround Strataworx Blue Herring



Surround Strataworx Raven



Surround Strataworx Limestone



Surround Strataworx Storm Cloud

Suitable for all commercial applications such as:

>Education

>Retail

>Workplace

Disclaimer: The colour images provided are indicative only and installed for creative purposes and not according to technical specifications. Please refer to Shaw Contract installation instructions for guidance.

Jacobsen® | ShawContract®

Talk to one of our experts, or visit our website:

0800 800 460 | jacobsen.co.nz | customer.services@jacobsen.co.nz



	Poured Strataworx	Diffuse Strataworx	Surround Strataworx
Style Number	5T431	5T430	5T432
Construction	Multilevel Pattern Loop	Multilevel Pattern Loop	Multilevel Pattern Loop
Fiber	EcoSolution Q® Nylon	EcoSolution Q® Nylon	EcoSolution Q® Nylon
Primary Backing	Synthetic	Synthetic	Synthetic
Secondary Backing	Strataworx® Tile	Strataworx® Tile	Strataworx® Tile
Protective Treatments	SSP® Shaw Soil Protection	SSP® Shaw Soil Protection	SSP® Shaw Soil Protection
Product Size	610mm x 610mm	610mm x 610mm	610mm x 610mm
Area per carton	7.43m ²	7.43m ²	7.43m ²
Pieces per carton	20	20	20
Gauge	47.2 per 10cm (1/12in)	47.2 per 10cm (1/12in)	47.2 per 10cm (1/12in)
Stitches	33.0 per 10cm (8.5 per in)	34.0 per 10cm (8.5 per in)	36.5 per 10cm (9.0 per in)
Finished Pile Thickness	1.98mm	2.34mm	2.13mm
Total Thickness	5.79mm	5.84mm	5.64mm
Tufted Weight	16oz	16oz	15oz


Performance & Testing

Electrostatic Propensity	Less than 3.5 kv	Less than 3.5 kv	Less than 3.5 kv
Reaction to Fire ISO9239.1:2010	6.3 kW/m ² Lok Dots 6.4 kW/m ² Direct Stick	6.3 kW/m ² Lok Dots 6.4 kW/m ² Direct Stick	6.3 kW/m ² Lok Dots 6.4 kW/m ² Direct Stick
Warranty	15 years Commercial Limited	15 years Commercial Limited	15 years Commercial Limited


Environmental Certification Poured/Diffuse/Surround

Cradle to Cradle Certified™			
Health Product Declaration (HPD)			
Environmental Product Declaration (EPD)			
Living Building Challenge (LBC)			
Declare			
NSF 140			
Singapore Green Label			
Green Label Plus Certification			
Total Recycled Content	33%	33%	33%


Recommended Installation Method




Quarter Turn




Random



Monolithic



Brick



Ashlar

The information in this data sheet is correct at date of publication however, due to Shaw Contract's commitment for ongoing product improvement, we reserve the right to change this information without notice. Please note that Shaw Contract's instructions regarding installation, cleaning and maintenance must be observed.

* Random layout for Poured and Diffuse only

Jacobsen® | ShawContract®

Talk to one of our experts, or visit our website:

0800 800 460 | jacobsen.co.nz | customer.services@jacobsen.co.nz

