

# iQ EMINENT

## TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	iQ Eminent
<b>Type of floor covering</b>	EN 14565	Homogeneous single layered vinyl flooring
<b>Binder content</b>	ISO 10581	Type I
<b>CE certification</b>	EN 14041	Yes
<b>Classification</b>	ISO 10874	Commercial: 34 Industrial: 43

  

TECHNICAL CHARACTERISTICS	STANDARDS	iQ Eminent
<b>iQ surface treatment</b>		Yes
<b>Total thickness</b>	ISO 24346	2.0 mm
<b>Total weight</b>	ISO 23997	2800 g/m <sup>2</sup>
<b>Form of delivery</b>	ISO 24341 Sheet (rolls)	Approx. 23 lm x 200 cm Art. no. 21030_ _ _ 3 digit colour colour number

	STANDARDS	iQ Eminent
<b>Dimensional stability</b>	ISO 23999	≤ 0.40% for rolls ≤ 0.25% for tiles
<b>Reaction to fire</b>	AS/ISO 9239.1 AS/NZ 3837 (wall)	Critical radiant flux 10.2kW/m <sup>2</sup> Smoke 213%.min Group 3
<b>Residual indentation</b>	ISO 24343-1	Required value: ≤ 0.10 mm Best measured value: 0.02 mm
<b>Castor c</b>	ISO 4918	Suitable
<b>Ease of decontamination</b>	ISO 8690	Excellent
<b>Static electrical discharge</b>	EN 1815	< 2 kV
<b>Clean room</b>	ISO 14644-1 ISO ASTM F24 F51	ISO class 4 Class A
<b>Total VOC emissions</b>	AgBB/DIBt Indoor air quality FloorScore RTS emission class	≤ 10 µg/m <sup>3</sup> (after 28 days) Platinum SCS certified M1
<b>Underfloor heating</b>		Suitable – max 27°C
<b>Thermal resistance</b>	EN 12667	Approx. 0.01 m <sup>2</sup> K/W
<b>Light fastness</b>	EN ISO 105-B02	≥ level 6
<b>Chemical resistance</b>	ISO 26987	Excellent
<b>Bacteria resistance</b>	EN ISO 846:Part C	Does not favour growth
<b>Slip resistance</b>	DIN 51130 AS 4586	R10 P4
<b>Wet room approval</b>	N 13553 Annex A GBR approval system	Watertight Certified
<b>Abrasion</b>	EN 660:Part 2	≤ 2.0 mm <sup>3</sup>
<b>Flexibility</b>	ISO 24344	Pass
<b>Seam strength</b>	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
<b>Colours</b>		34

The above information is subject to modification for the benefit of further improvement. (01/17).

CUSTOMS TARIFF : 482050000000F

Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for these instructions.



According to European Classification ISO 10874 - EN 685

