# Jacobsen®

### Product Information Declaration

## **Audacity Laminate Range**

1

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as Audacity Laminate

#### Scope and Limitations of Intended Use

~	Residential
~	High Traffic
×	Antistatic Environment
x	Ramp/Entry

X Low Traffic X Food Prep Areas

Commercial

- Under Floor Heating
- ✓ Interior
   ✓ Exposed Sunlight

**Identifiers** 

See individual sku codes under identifiers

X Glean Room

**Over Existing Floor** 

iyin

- X Exterior
- X Wet Areas
- With Wheels

## B

#### Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	5 Years Commercial Limited, 15 Years Residential Limited	
Residential	AC4	
Commercial	AC4	
Industrial	-	

#### C Protection from Fire

 Relevant NZBC Clause
 Product Performance

 C4.3

 C4.3 (a) Wall

 C4.3 (b) Floor
 > 11 (EN ISO

9239-1:2010)

Х

### D Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

### Ε

#### Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

## н

#### **Energy Efficiency**

Relevant NZBC Clause	Product Performance	
Thermal Rating	Not tested	

## F

Χ

#### Safety of Users

Warnings and Bans

Building Act 2004

Section 26

Relevant NZBC Clause	Product Performance	
F2.3.1	≤ 0.5mg/m3 (CDPH/ EHLB v1.2-2017)	
	Does not encourage bacterial growth	
	Phthalate-free	
Indoor Air Quality	Optimal	

Product Performance

### G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



### **Product Information Declaration Audacity Laminate Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### Note

It is expected that **Audacity Laminate** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

### **Product Information Declaration Audacity Laminate Range**

#### **Identifiers**

This JPID covers all colours from Audacity Laminate including:

Castle Point 21415 Fiordland 21412 Mercury Bay 21411 Helena Bay 21410 Riverton 21409 Victorian Oak 21404 Milford 21403 American Oak 21402 London Fog 21400 Foxton 21399 Eden 21398 Longwood 21397

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Decele	-	
Embodied Carbon Emission Da	-	

#### **Environmental Credentials**



## Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: China Floors Country of Origin: China