



Silent Shield

Helix Rubber

Regupol 4515

Recommended for use under	Laminate		Laminate Engineered Wood Homogeneous Vinyl Sheet	Laminate Engineered Wood Homogeneous Vinyl Sheet (4515-S) Ceramic Tiles Glue Down LVT		
Material	Crosslinked polymeric foam with polymeric film		90% recycled rubber crumb 10% PET	PUR foam and cork, bound with polyurethane		
Thickness	2mm		2mm	4.5mm (4515-S; 3mm)		
Width	1000mm		1000mm	1000mm		
Roll Length	30m		15m	20m		
Application	Residential, Commercial		Residential, Commercial	Residential, Commercial		
Installation	Floating only		Floating or Glue down	Floating or Glue down		
Environmental			PVC free	Good Environmental Choice Australia ISO14001 PVC free		
Approximate acoustic dB reduction (compared to bare concrete floor)	12.5mm Wood	-	with Helix	16 dB	-	
	14mm Wood	-	with Helix	15 dB	with Regupol 4.5mm 17 dB	
	8mm Laminate	with Silent Shield	18 dB	with Helix	17 dB	with Regupol 4.5mm 19 dB
	2mm Vinyl Sheet	-	-	with Helix	17 dB	with Regupol 4515-S 3mm 17 dB
	10mm Ceramic Tile	-	-	-	-	with Regupol 4.5mm 17 dB
	2mm LVT	-	-	-	-	with Regupol 4515-S 3mm 18 dB

Refer to www.jacobsens.co.nz/downloads/accessories for full test results.



www.studioflooring.co.nz



www.jacobsens.co.nz