

ACCZENT RUBY

Heterogeneous compact floor vinyl



Solid performing vinyl floor for heavy traffic areas

Flooring for heavy duty commercial and heavy industrial areas, featuring bright mineral and realistic wood designs.

TOP CLEAN

Reduced Life Cycle Cost

TopClean surface provides easy cleaning and maintenance, with no need for wax or polish.

LOW VOC

Improved Indoor Air

Phthalate free, with very low VOC emissions, giving a better quality indoor environment.

LONG WEAR

Heavy Duty Traffic

Commercial grade 0.7mm wear layer for excellent stain and scratch resistance.

Product Characteristics	Standard	Acczent Ruby
Product construction	EN 649	Heterogeneous compact vinyl flooring
Classification	EN 685	Commercial : 34, Industrial: 43
Surface treatment		TopClean
Total thickness	ISO 24346 (EN 428)	2.0mm
Wear layer thickness	ISO 24340 (EN 429)	0.7mm
Total weight	ISO 23997 (EN 430)	3000g/m ²
Form of delivery	ISO 24341 (EN 426)	Approx. 23 lm x 2 m
Warranty		10 years
Available colours		36
Underfloor heating		Suitable

Performance Characteristics	Standard	Acczent Ruby
Reaction to fire	ISO 9239-1	Critical radiant flux 8.2 kW/m ² Smoke 193%.min
Slip resistance	AS/NZS 4586 - Appendix A (wet) AS/NZS 4586 - Appendix D (oil/wet)	SRV 33 - not suitable for wet areas R10
Electrostatic Properties	EN 1815/ EN 1081	< 2 kV on concrete/ R1 > 10 ⁹ Ω
Total VOC emissions	AgBB/DIBt	≤ 100 µg/m ³ (after 28 days)
Thermal resistance	EN 10456	0.02 m ² K/W
Chemical resistance	ISO 26987 (EN 423)	High resistance
Hygiene	-	Does not contribute to infection spreading
Dimensional stability	ISO 23999 (EN 434)	≤ 0.10%
Abrasion Group	EN 660: Part 2	Group T: ≤ 2.0mm ³
Residual indentation	ISO 24343-1 (EN 433)	≤ 0.10 mm
Castor chair test	ISO 4918 (EN 425)	No damage
Furniture leg test	EN 424	No damage
Curl resistance to heat	ISO 23999 (EN 434)	≤ 8mm
Light fastness	EN ISO 105-B02	≥ level 6