


## tile specifications

style name	diffuse tile	
style number	59575	
construction	multi-level pattern loop	
fiber	eco solution q® nylon	
dye method	100% solution dyed	
	<b>u.s.</b>	<b>metric</b>
-----		
pattern repeat	none	
tufted weight	16.0	542.49 g/m <sup>2</sup>
gauge	1/12	47.24 per 10 cm
stitches per inch	9.0	35.43 per 10 cm
finished pile thickness	0.092	2.34 mm
total thickness	0.230	5.84 mm
average density	6261	11.66 kilotex
product size	24" x 24"	60.96 cm x 60.96 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments	ssp® shaw soil protection	
gsa approved product	yes	

## testing

radiant panel	Class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

## warranties

lifetime commercial limited

## installation method



## coordinating products

shadow play tile, blox tile, color play tile, kinetic tile, simply done tile, nothing to it tile, captivate tile, intrigue tile, disperse tile, chroma tile, spectrum tile, tempt tile

## environmental certification

green label plus certification number	glp9968
nsf140 gold	
cradle to cradle silver certified	



Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

eco impacts

---

**end of life**

**environmental guarantee**

free pick up & recycling

To recycle call 800.509.Shaw or +86 400 800 Shaw (Asia Pacific)

---

**materials**

**ingredients**

face fiber	nylon 6
dye method	100% solution dyed
backing	polyolefin composite
surface treatments	non c8 fluorocarbon chemistry
does not contain PVC, phthalates, or PBD/PBDE	

**recycled content**

total recycled content (by weight)	36.2 %
pre-consumer	36.2 %
post-consumer	0.0 %
bio-based/rapidly renewable content (by weight)	0.0 %
packaging	100% recyclable
country of origin (manufacturer)	USA

Meets or exceeds all local and national regulations in country of manufacture.

Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.

Recycled content is calculated using system allocation, mass balance, and direct insertion.

The actual recycled content in this product will likely vary. For more information email

info@shawgreenedge.com.

---

**third party certifications**

MBDC cradle to cradle	silver certified
NSF 140	gold certified
CRI green label plus	GLP9968
USGBC LEED	contributes