


# GRANIT MULTISAFE

## Waterproof homogeneous studded floor vinyl



### Waterproof vinyl flooring for enhanced wet barefoot slip resistance in bathroom areas

Flooring for commercial wet barefoot areas, colour coordinated to the iQ Granit range featuring a studded surface.

STUDED SURFACE	LOWEST VOC	GRANIT DESIGN
<p><b>Barefoot Safety</b></p> <p>Easy clean rounded studs for comfortable barefoot slip resistance in wet rooms.</p>	<p><b>Optimal Indoor Air</b></p> <p>Phthalate free, with VOC emissions below quantifiable levels, giving the best quality indoor environment.</p>	<p><b>Co-ordinated Style</b></p> <p>Keep a consistent look throughout the facility with various Granit finishes designed for specific areas.</p>

Product Characteristics	Standard	Granit Multisafe
Product construction	EN 649	Homogeneous vinyl flooring with studded surface
Classification	EN 685	Commercial : 31
Total thickness	ISO 24346 (EN 428)	2.0mm (2.5mm including raised profile)
Wear layer thickness	ISO 24340 (EN 429)	2.0mm
Total weight	ISO 23997 (EN 430)	3010g/m <sup>2</sup>
Form of delivery	EN 426	Approx. 25lm x 2 m
Warranty		10 years
Available colours		13
Underfloor heating		Suitable – max 27°C

Performance Characteristics	Standard	Granit Multisafe
Reaction to fire	ISO 9239-1	Critical radiant flux 10.8kW/m <sup>2</sup>
Slip resistance	AS/NZS 4586 - Appendix A (wet) AS/NZS 4586 - Appendix C (wet barefoot) AS/NZS 4586 - Appendix D (oil/wet)	SRV 43 C R10
Static electrical discharge	EN 1815	< 2kV
Total VOC emissions	AgBB/DIBt	≤ 10µg/m <sup>3</sup> (after 28 days)
Thermal resistance	EN 12667	Approx. 0.01m <sup>2</sup> K/W
Chemical resistance	ISO 26987 (EN 423)	Good resistance
Fungi and bacteria resistance	ISO 846: Part C	Does not favour growth
Dimensional stability	ISO 23999 (EN 434)	≤ 0.40%
Abrasion Group	EN 660: Part 2	Group T: ≤ 2.0mm <sup>3</sup>
Residual indentation	ISO 24343-1 (EN 433)	Approx. 0.02mm
Light fastness	EN ISO 105-B02	≥ Level 6
Seam strength	EN 684	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm