

HETEROGENEOUS
ACOUSTIC VINYL

Tapiflex Excellence 65

Specification

Printed acoustic vinyl floorcovering with high density foam backing on a glass fibre stabilized carrier, filler free wear layer. PUR reinforcement, built in fungistatic and bacteriostatic Sanitized® treatment.
Product standard : EN 651.

HETEROGENEOUS
COMPACT VINYL

Accent Excellence 80


Specification

Printed compact vinyl floorcovering on glass fibre stabilized carrier, filler free wear layer. PUR reinforcement, built in fungistatic and bacteriostatic Sanitized® treatment.
Product standard: EN 649.

CERTIFICATION & CLASSIFICATION	STANDARDS	Tapiflex Excellence 65 (Sheet)	Tapiflex Excellence 65 (Tiles)	Accent Excellence 80 (Sheet)
Type of floorcovering	EN 651 EN 649	Heterogeneous Acoustic Vinyl	Heterogeneous Acoustic Vinyl	Heterogeneous Compact Vinyl
CE certification	EN 14041	Yes	Yes	Yes
UPEC classification		U4P3E2/3C2	U4P3E2/3C2	U4P3E2/3C2
Impact sound reduction	EN ISO 140-8 EN ISO 717-2	ΔL_w 19 dB	ΔL_w 19 dB	ΔL_w 4 dB
Acoustical improvement	NF S31-074	$L_{n,e,w}$ = 61 dB	$L_{n,e,w}$ = 61 dB	$L_{n,e,w}$ = 77 dB
NF UPEC. A+ certificate	NF 189	305-078.1	305-080.1	305-070.1 (NF UPEC)
Classification	EN 685	34	34	34-43
TECHNICAL CHARACTERISTICS	STANDARDS	Tapiflex Excellence 65 (Sheet)	Tapiflex Excellence 65 (Tiles)	Accent Excellence 80 (Sheet)
Wear layer thickness	EN 429	0.65 mm	0.65 mm	0.80 mm
Surface treatment		TopClean XP	TopClean XP	TopClean XP
Total thickness	EN 428	3.45 mm	3.55 mm	2.00 mm
Abrasion group	EN 660-1	Group T : $\leq 0,08$ mm	Group T : $\leq 0,08$ mm	Group T : $\leq 0,04$ mm
Total weight	EN 430	3 295 g/m ²	3 465 g/m ²	3 100 g/m ²
Form of delivery	EN 426 Sheet (rolls) EN 427 Tiles (box)	approx. 23 running metres x 200 cm	50 x 50 cm - 20 tiles/box = 5.00 m ²	approx. 23 running metres x 200 cm
TECHNICAL PERFORMANCES	STANDARDS	Tapiflex Excellence 65 (Sheet)	Tapiflex Excellence 65 (Tiles)	Accent Excellence 80 (Sheet)
Dimensional stability	EN 434	< 0.10%	< 0.10%	< 0.10%
Reaction to fire	EN 13501-1	B _{f1} s1 on fibre cement substrate A2 _{f1} C _{f1} s1 on woodchip substrate	B _{f1} s1 on fibre cement substrate A2 _{f1} C _{f1} s1 on woodchip substrate	B _{f1} s1 on fibre cement substrate A2 _{f1} and on woodchip substrate
Static indentation	EN 433	0.15 mm	0.15 mm	0.03 mm
Castor chair	EN 425	No damage	No damage	No damage
Underfoot comfort	EN 433	≥ 0.40 mm	≥ 0.40 mm	Not applicable
Furniture leg	EN 424	No damage	No damage	No damage
Curl resultant to heat	EN 434	≤ 8 mm	≤ 8 mm	≤ 8 mm
Electrostatic properties	EN 1815 EN 1081 EN 14041	< 2 kV R1 > 10 ¹⁰ Ω Antistatic on concrete	< 2 kV R1 > 10 ¹⁰ Ω Antistatic on concrete	< 2 kV R1 > 10 ¹⁰ Ω Antistatic on concrete
Fungi static and bacteria static effect	NF EN ISO 846	Sanitized®	Sanitized®	Sanitized®
Chemical resistance	EN 423	High resistance	High resistance	High resistance
Thermal resistance	EN 12524	0,05 m ² K/W Suitable	0,05 m ² K/W Suitable	0,03 m ² K/W Suitable
Underfloor heating				
Light fastness	EN ISO 105-B02	$\geq 6/8$	$\geq 6/8$	≥ 6
Slip resistance	DIN 51130 EN 13893	R9 $\geq 0,3$	R9 $\geq 0,3$	R9 $\geq 0,3$
Colours		100	10	51

The above information is subject to modification for the benefit of further improvement (01/10).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett for these instructions.



Italy: Tarkett Australia Pty Ltd - Tel. +61 2 96 34 73 73 • Austria: Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 478 80 62 • Baltic States: Tarkett Wyk_adziny Sp. z o.o. - Tel. +370 37 262 220 • Belgium: S.A. Tarkett Tel. +32 16 35 98 80 • Brazil: Tarkett FADEMAM - Tel. +55 12 3954 7244 • Canada: Tarkett Inc. - Tel. +1 450 293 173 • China: Tarkett Asia Pacific Limited - Shanghai Representative Office - Tel. +86 21 60 95 6838 / +86 21 6859 • Czech Republic: Tarkett SAS, org. slozka - Tel. +420 271 001 602 • Denmark: Tarkett A/S - Tel. +45 43 90 60 11 • Finland: Tarkett Oy - Tel. +358 9 5406 5870 • France: Tarkett France - Tel. +33 1 41 20 42 49 many: Tarkett Holding GmbH, Bereich Objekt - Tel. +49 (0) 62 33 810 • Greece: Tarkett Monoprosopi Ltd - Tel. +30 2 10 576 3889 • Hong Kong: Tarkett Asia Pacific Ltd. - Tel. +852 251 18 716 • Hungary: Tarkett SAS - Tel. +36 1 8150 • Italy: Tarkett S.p.A. - Tel. +39 02 893 411 • Luxembourg: Tel. +352 949 211 8804 • Middle East: Tarkett Middle East - Tel. +961 151 3363/4 • Netherlands: Tarkett Holding GmbH - Vestiging Nederland - Tel. +31 80 760 • Norway: Tarkett AS - Tel. +47 32 20 92 00 • Poland: Tarkett Wyk_adziny Sp. z o.o. - Tel. +48 22 639 31 66 • Portugal: Tarkett SA - Tel. +351 21 427 64 20 • Russian Federation: Tarkett Russia - Tel. +7 4 95 777 69 Slovakia: Tarkett SAS - Tel. +421 248 291 317 • Singapore: Tarkett Far East - Tel. +65 67 43 53 84 • South East Europe: Tarkett Trade d.o.o. - Tel. +381 21 7557 649 • Spain: Tarkett Floors S.L - Tel. +34 91 358 00 35 • Sweden: Tarkett Sverige AB - Tel. +46 771 25 19 00 • Switzerland: Tarkett Holding GmbH, Bereich Objekt Schweiz - Tel. +41 (0) 43 233 79 24 • Turkey: Tarkett ASPEN - Tel. +90 212 213 65 80 • Ukraine: Tarkett UA - Tel. +380 (44) 569 12 United Kingdom: Tarkett Ltd - Tel. +44 (0) 1622 854 040 • North America: Johnsonite - Tel. +1 440 543 8916 • Tarkett Inc. USA - Tel. +1 713 869 5811 • Latin America: Tarkett FADEMAM - Tel. +55 12 3954 7244 • Tarkett national: Tel. +33 1 41 20 41 01