



HI-PERFORMANCE CARPET TILE ADHESIVE

Designed for use with **eco•worx®**

Description

SureTac™ PSi is a high performance, permanently pressure sensitive, interior carpet tile adhesive that has a minimal impact on the environment.

SureTac™ PSi is formulated to be applied to Shaw hi-performance carpet tiles made using the environmentally innovative EcoWorx® backing. Its unique formula means carpet tiles installed using SureTac™ PSi can be removed and replaced as often as required while retaining its pressure sensitive characteristics for the lifetime of the carpet.

Features



GBCA IEQ-13 COMPLIANT



ECOSAC™/REUSABLE/RECYCLABLE PAIL



WATER BASED/SOLVENT FREE



ANTISTATIC



ANTIMICROBIAL

Physical Properties:

Appearance	Green
Base	Acrylic Latex
Viscosity	15,000 to 20,000 cps at 25°C
Specific Gravity	1.00
Solids	50±1%
Tack-Up	30-60 minutes to indefinite at 20°C dust free
Coverage	8 - 12 m ² per litre
Shelf Life	12 months in unopened containers at 20°C. Do not allow to freeze
Available in	10 litre pail

Clean Up:

Use water to remove excess adhesive while it is still wet.

Safety & First Aid:

Avoid contact with eyes and skin, Avoid breathing adhesive vapour. Wear eye and skin protection when handling. If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If eye contact occurs, hold eyes open and flush with water for 15 minutes. If swallowed, do not induce vomiting and consult a doctor immediately.



Surface Preparation:

All surfaces must be clean, dry, sound and smooth. They should be free of contaminants such as wax, grease, paint, old adhesive, dust and dirt, oil and sealers.

All sub floors must be structurally sound prior to applying the adhesive, and free of voids and loose materials. Porous substrates must be sealed with a suitable acrylic based primer and allowed to dry before applying SureTac™ P*Si*.

Suitable non porous sub floors must be sealed with a non porous primer and allowed to dry. Once dry, an engineered cement levelling compound should be applied to the sub floor.

Uneven or damaged floors must also be repaired with an engineered self levelling compound. Structural particle and flooring boards should be sanded with a coarse grit paper. Once sanded, prime the sub floor with a suitable acrylic based primer.

New concrete sub floors must be completely cured. Always ensure that concrete sub floors are free from laitance (friable surface), curing compounds and bond breakers. If these materials are apparent, they must be mechanically removed and the sub floor made good before applying SureTac™ P*Si*.

All sub floors should be tested with a moisture reading device as per Australian Standard 1884:1985. The sub floor shall be considered acceptable when the moisture content does not exceed 5.5% or the relative humidity does not exceed 70%.

All substrates must be in accordance with the current Australian Standards.

WARNING:

Do not apply if temperature is below 10°C or above 28°C.

This adhesive will not operate under hydrostatic pressure or capillary action.

Application:

Refer to the Shaw EcoWorx® hi-performance carpet tile installation guide.

1. Application of adhesive in ambient temperature environments below 15°C, apply the adhesive to the sub-floor with a U1 (0.8x0.8x1.6mm) U notch trowel.
Coverage; approximately 8m²/litre.
 2. Application of adhesive in ambient temperature environments above 15°C, apply the adhesive to the sub-floor with a medium nap roller.
Coverage; approximately 12m²/litre.
 3. Allow the adhesive to develop a dry tacky film prior to installing the carpet tiles as per installation instructions.
 4. Ensure the carpet tiles make good contact with the dry adhesive by rolling them as per installation instructions.
 5. Once the tiles are installed do not allow heavy traffic for 24 hours.
-

THE STATEMENTS AND TECHNICAL INFORMATION CONTAINED IN THIS DOCUMENT ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE BUT WHOSE ACCURACY IS NOT GUARANTEED. USERS ASSUME ALL RISK AND LIABILITY RESULTING FROM THE USE OF THIS PRODUCT AND MUST CONFIRM ITS SUITABILITY BY THEIR OWN TESTS. CONDITIONS OF SALE CONTAIN A LIMITED WARRANTY AGAINST MANUFACTURING DEFECTS.

Further Information:

Shaw Contract Group Australia

T: 1800 556 302

E: info@shawcontractgroup.com.au

W: www.shawcontractgroup.com.au.com.au



green building council australia
MEMBER

VOC Content Test Certificate

Tuesday July 21st, 2009

Manufacturer: Holdfast Adhesives Australia Pty Ltd (90 – 92 Bay Street, Botany NSW 2019)

Sample Description: SureTac PSi carpet tile adhesive

Date Tested: July 2009 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: SCAQMD Method 304-91 Determination of Volatile Organic Compounds (VOC) in Various Materials as referenced by South Coast Air Quality Management Division (SCAQMD) Rule 1168.

Test Data:

Specification Green Building Council of Australia Green Star Office Design V2 IEQ-13 Green Star Office Interiors V1.1 IEQ-11	SureTac PSi
Indoor Carpet Adhesive 50 grams per Litre as VOC content material	<10 grams per Litre as VOC content material
Specification Green Building Council of Australia Green Star Office Design V3 IEQ-13	SureTac PSi
Indoor Carpet Adhesive 50 grams per Litre as VOC content material	<10 grams per Litre as VOC content material



Dr. Vyt Garnys
PhD, BSc(Hons) AIMM, ARACI, ISIAQ
ACA, AIRAH, FMA
Managing Director and Principal Consultant

F0907-12

MATERIAL SAFETY DATA SHEET
SureTAC PSI ADHESIVE

Issue Date: 1st February 2010

Section 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SURETAC PSI ADHESIVE

SYNONYMS

“One part solvent free PS adhesive”

PRODUCT USE

For bonding carpet tiles.

SUPPLIER

Company: Shaw Contract Group Australia Pty Ltd
Address: Unit 13 3 Rocklea Drive Port Melbourne VIC 3207
Telephone: +61 3 9939 8543
Emergency tel: +61 3 9939 8543
Fax: +61 3 9939 8549

Section 2 – HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANDEROUS GOODS. According to the Criteria of NOHSC and the ADG Code.

POISONS SCHEDULE

None

RISK

May produce discomfort of the eyes,
respiratory tract & skin*
Possible skin sensitiser*
* (limited evidence)

SAFETY

Avoid contact with skin

Wear eye/face protection
In case of contact with eyes rinse with plenty of
water and contact Doctor or Poisons Information
Centre.

Section 3 – COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL ENTITY	CAS NO.	PROPORTION
Ingredients determined to be non hazardous		100%

SURETAC PSI ADHESIVE

Section 4 – FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; ie. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as patient can comfortably drink.
- Seek medical advice.

EYE

- If this product come in contact with the eyes:
- Wash our immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs;

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled, remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth (which may block airway) should be removed, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

SURETAC PSI ADHESIVE

FIRE FIGHTING

- Alert the Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.
- Decomposes on heating and produces toxic fumes of: carbon dioxide (CO₂), nitrogen oxides (NO_x). Products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

HAZCHEM: None

Section 6 – ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety goggles.
- Trowel up/scrape up.
- Place spilled material in clean, dry, sealed container.
- Flush spill area with water.

MAJOR SPILLS

- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS

SURETAC PSI ADHESIVE

Section 7 – HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia)

SURETAC PSI ADHESIVE

PERSONAL PROTECTION

EYE

- Safety glasses with side shields
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation – lens should be removed in a clean environment only after workers have washed hands thoroughly. (CDC NIOSH Current Intelligence Bulletin 59).

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Green paste; soluble in water.

SURETAC PSI ADHESIVE

PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: Not Applicable	Boiling Range (°C): >100
Melting Range (°C): 45-115	Specific Gravity (water=1): -1.0
Solubility in water (g/L): Miscible	pH (as supplied): Not Applicable
pH (1% solution): Not Available	Vapour Pressure (kPa): Not Available
Volatile Component (%vol): Not Available	Evaporation Rate: Not Available
Relative Vapour Density (air=1): Not Available	Flash Point (°C): Not Applicable
Lower Explosive Limit (%): Not Available	Upper Explosive Limit (%): Not Available
Autoignition Temp (°C): Not Available	Decomposition Temp (°C): >180
State: Non Slump Paste	Viscosity: Not Available

Section 10 – CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

Product is considered stable and hazardous polymerisation will not occur.

For incompatible materials – refer to Section 7 – Handling and Storage.

Section 11 – TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Considered an unlikely route of entry in commercial/industrial environments. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

EYE

- There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

- There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

INHALED

- Not normally a hazard due to non-volatile nature of product. The vapour is discomforting. Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

- There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

SURETAC PSI ADHESIVE

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.
- Not available for mixture or identified for ingredient(s).

Section 12 – ECOLOGICAL INFORMATION

Do not discharge into sewer or waterways.

Section 13 – DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 – TRANSPORTATION INFORMATION

HAZCHEM: None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 – REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

(CAS: None):

No regulations applicable

Section 16 – OTHER INFORMATION

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since we cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.