



Silent Shield

Regupol 4515

Recommended for use under		Laminate		Laminate Engineered Wood Homogeneous Vinyl Sheet (4515-S) Ceramic Tiles Glue Down LVT	
Material		Crosslinked polymeric foam with polymeric film		PUR foam and cork, bound with polyurethane	
Thickness		2mm		4.5mm (4515-S); 3mm	
Width		1000mm		1000mm	
Roll Length		30m		20m	
Application		Residential, Commercial		Residential, Commercial	
Installation		Floating only		Floating or Glue down	
Environmental		-		Good Environmental Choice Australia ISO14001 PVC free	
Approximate acoustic dB reduction (compared to bare concrete floor)	12.5mm Wood	-		-	
	14mm Wood	-		with Regupol 4.5mm	17 dB
	8mm Laminate	with Silent Shield	18 dB	with Regupol 4.5mm	19 dB
	2mm Vinyl Sheet	-		with Regupol 4515-S 3mm	17 dB
	10mm Ceramic Tile	-		with Regupol 4.5mm	17 dB
	2mm LVT	-		with Regupol 4515-S 3mm	18 dB

Refer to www.jacobsens.co.nz/downloads/accessories for full test results.



www.studioflooring.co.nz



www.jacobsens.co.nz